#### **Post Holders**



# Post Holder RDS

The RDS post holders (including base) are suitable for post dimensions from 11 to 15 mm diameter. Very stable through a precise three-point-support. They are compatible to posts and post holders on the market.

# Clearence hole (100% of the height is usable) Magnetic base (for fast mounting)

Size	Inner lower- ing for M6 or M8 screws	With M6 thread	Clearance Hole 15 mm	Magnetic Base
25 mm			RDS-H-25	RDS-M-25
35 mm	RDS-35	RDS-T-35	RDS-H-35	RDS-M-35
40 mm	RDS-40	RDS-T-40	RDS-H-40	RDS-M-40
50 mm	RDS-50	RDS-T-50	RDS-H-50	RDS-M-50
75 mm	RDS-75	RDS-T-75	RDS-H-75	RDS-M-75
100 mm	RDS-100	RDS-T-100	RDS-H-100	RDS-M-100





#### **RD-SB**

 Mounting Screw with ball, which is under spring tension to preadjust the post height.

# **Post Holder without Base**

- Post Holder without base
- M6 thread on the bottom
- Suitable for post from 11 to 15 diameter

Size	Order Number
25 mm	RDS-OF-25
40 mm	RDS-OF-40
65 mm	RDS-OF-65
90 mm	RDS-OF-90



#### Post Holder Base for RDS-OF

#### RDS-F

- Base for RDS-OF
- Height 4,5 mm
- With M6 thread



# **Mounting Bases for Post Holders and Pedestals**

RD-MB-2 (76 mm x 26 mm x 10 mm)

(58 mm x 25 mm x 10 mm) RD-MB-1



#### **Posts RD-GS**

Stainless steel posts

Diameter

- Posts fit to all post holders
- Standard M4 inside threads on the one side and M6 on the other side

Order number

One grub screw (M4) including Size

0.00	
50 mm	RD-GS-50 Ø 0,5 inch
75 mm	RD-GS-75 Ø 0,5 inch
100 mm	RD-GS-100 Ø 0,5 inch
Size	Order number
50 mm	RD-GS-50 Ø 13 mm
75 mm	RD-GS-75 Ø 13 mm
100 mm	RD-GS-100 Ø 13 mm
Size	Order number
50 mm	RD-GS-50 Ø 15 mm
75 mm	RD-GS-75 Ø 15 mm
100 mm	RD-GS-100 Ø 15 mm
	75 mm 100 mm  Size 50 mm 75 mm 100 mm  Size 50 mm 75 mm 75 mm



# **Connectors & Holding Forks**

#### **Post Holder Connector**

#### **RD-PHC**

 90° connection between two posts





Mounting option

# **Holding Forks RDK-1**

RDK-1 Holding Fork, flexible and stable fixing of all RDS, RDS-G and RDS-OG post holders and pedestals through precise three-point-support.

Compatible to other pedestals on the market.

- RDK-1 mini
- RDK-1 midi
- RDK-1 maxi



# **Holding Forks RDK-2**

RDK-2 Holding Fork, flexible and stable fixing of RDS-G pedestals

For RDS-G Pedestals:

**RDK-2 midi** (Ø 25 mm)

For RDS-G-B Pedestals:

**RDK-2 maxi** (Ø 51 mm)



#### **Clamping Forks RD-PH**

RD-PH clamping fork, stable fixing of our RD1 and RD2 Mirror Mounts:

• **RD-PH-1** (38 mm x 16 mm x 9 mm)

• **RD-PH-2** (50 mm x 19 mm x 17 mm)

• **RD-PH-3** (50 mm x 19 mm x 23 mm) for RD2

• **RD-PH-4** (50 mm x 12 mm x 8 mm ) for RD1



#### **Table Clamps RD-TC**

Table Clamp to fix several optomechanics on the table.



RD-TC-B RD-TC-S RD-TC-D

# Base Plates and Height Adapter for RD1 and RD2

**Base Plate:** 

for RD1 Mirror Mounts:

RD1-GP

for RD2 Mirror Mounts:

RD2-GP

**Height Adapter:** 

for RD1 Mirror Mounts:

RD1-HA1 beam height 50 mm

for RD2 Mirror Mounts:

RD2-HA1 beam height 75 mm

RD2-HA2 beam height 100 mm



The heights are always total heights:

Beam height=

Base plate + height adapter + mirror mount

#### Base Plates & Height Adapters for MNI, MNI-HS, MDI, MDI-H(S), MXI

#### MNI Base plate:

 Available with long hole in longitudinal direction or with long holes in crosswise direction

#### **MNI** Height Adapters:

- For 50 mm beam height
- For 75 mm beam height

#### MDI Base plate:

- Available with long hole in longitudinal direction
- Available with long holes in crosswise direction

#### MDI Height Adapters:


- For 50 mm beam height
- For 75 mm beam height

#### **MXI** Base plate:

- Available with long hole in longitudinal direction
- Available with long hole in crosswise direction

#### **MXI** Height Adapters:

- For 75 mm beam height
- For 100 mm beam height



The heights are always total heights:

Beam height=

Base plate + height adapter + mirror mount

#### Cap Screws, Washers & Set Screws

#### Cap screws

**RD-CS-M4-16** (M4 x16 mm)

RD-CS-M6-16 (M6 x 16 mm) RD-CS-M6-20 (M6 x 20 mm)

**Washers** 

RD-W-M4 (for M4 screws) RD-W-M6 (for M6 screws)



**RD-SC-M4-12** (length 12 mm) **RD-SC-M6-16** (length 16 mm)

Other length on request







#### **Pedestals**



All pedestals with thread (RDS-G and RDS-HS) can be combined with each other.

All Posts and Pedestals are also available with a lateral hole.

All pedestals are available made of POM.

All pedestals are available with a magnetic base for fast alignment.

(RDS-G-MA-...)

Mirror mounts can be fixed by a set screw or a cap screw





#### **RDS-MNI**

- Stainless steel pedestal
- Diameter 25.4 mm (∅ 1")
- The RDS-MNI system fits to our MNI mirror mounts
- Can be used on both sides
- Top side M4, bottom side M6 thread (standard)

#### Pedestal:

#### **RDS-MNI-P**

Size in mm	Order number
25	RDS-MNI-P-25
50	RDS-MNI-P-50
75	RDS-MNI-P-75

Other sizes on request

#### **Holding Fork:**

RDS-MNI-HF-S (small) RDS-MNI-HF-M (medium) RDS-MNI-HF-B (big)



# RDS-OG

- Diameter 25.4 mm (∅ 1")
- Pedestal with inner lowering for M4, M6 or M8 screws
- Available in aluminium, anodized aluminium or
- stainless steel

Size in mm	Size in inch	Order number
12.7	1/2	RDS-OG-0,5
19.1	3/4	RDS-OG-0,75
25		RDS-OG-25
25.4	1	RDS-OG-1
38.1	3/2	RDS-OG-1,5
50		RDS-OG-50
50.8	2	RDS-OG-2
63.5	5/2	RDS-OG-2,5
75		RDS-OG-75
76.2	3	RDS-OG-3
100		RDS-OG-100
101.6	4	RDS-OG-4
127	5	RDS-OG-5
152.4	6	RDS-OG-6

Other sizes on request



# RDS-G

- Diameter 25.4 mm (Ø1")
- Top side M4 thread (standard)
- Also available with M6 thread
- Available in aluminium, anodized aluminium or
- stainless steel

Size in mm	Size in inch	Order number
12.7	1/2	RDS-G-0,5
19.1	3/4	RDS-G-0,75
25		RDS-G-25
25.4	1	RDS-G-1
38.1	3/2	RDS-G-1,5
50		RDS-G-50
50.8	2	RDS-G-2
63.5	5/2	RDS-G-2,5
75		RDS-G-75
76.2	3	RDS-G-3
100		RDS-G-100
101.6	4	RDS-G-4
127	5	RDS-G-5
152.4	6	RDS-G-6

Other sizes or threads on request



# Pedestals & Height adjustable pedestals

# RDS-G-M

- Diameter 31.5 mm
- Pedestal with M4 (standard) or M6 thread on top
- Available in aluminium, anodized aluminium or
- stainless steel

Size in mm	Size in inch	Order number
25		RDS-G-M-25
25.4	1	RDS-G-M-1
38.1	3/2	RDS-G-M-1,5
50		RDS-G-M-50
50.8	2	RDS-G-M-2
63.5	5/2	RDS-G-M-2,5
75		RDS-G-M-75
76.2	3	RDS-G-M-3
100		RDS-G-M-100

Other sizes on request



#### RDS-G-B

- Diameter 51 mm
- Very stable pedestal with M4, M6 or M8 thread on top
- Available in aluminium, anodized aluminium or stainless steel
- Fits perfectly for our RD2 mirror mounts

Other sizes on request



#### RDS-HS

- Height adjustable pedestals
- Top side M4, bottom side M6 thread (standard)
- Easy to use
- Precise and ultra stable design

Available in the following sizes:		
Size in mm	Order number	
30-38 mm	RDS-HS-30-38	
38-50 mm	RDS-HS-38-50	
50-70 mm	RDS-HS-50-70	
55-80 mm	RDS-HS-55-80	
70 <b>-</b> 110 mm	RDS-HS-70-110	



eveloped by the University of Heidelberg. Inst. of Physics .AG Prof. Schmiedmaver by Dr. Alois Mair

# RDS-HSA

- Height adjustable adapter for pedestals
- Compatible to all pedestals
- Size 20-29 mm



### RDS-HA

- Height adjustable adapter for pedestals
- With M4 (standard) or M6 clearance hole
- Compatible to all pedestals
- Size 20-29 mm

Available in the following sizes:			
Size in mm	Order number ∅1"	Order number Ø 31.5 mm	
2 mm	RDS-HA-1"-2	RDS-HA-M-2	
3 mm	RDS-HA-1"-3	RDS-HA-M-3	
4 mm	RDS-HA-1"-4	RDS-HA-M-4	
5 mm	RDS-HA-1"-5	RDS-HA-M-5	
10 mm	RDS-HA-1"-10	RDS-HA-M-10	



# **Thread Adapters**

Av	Available in the following sizes:			
External Thread	Internal Thread	Length	Order Number	
M8	M6	9 mm	RD-TA-8-6-9	
M8	M6	6 mm	RD-TA-8-6-6	
M6	M4	8 mm	RD-TA-6-4-8	
M6	M4	6 mm	RD-TA-6-4-6	



# **Thread Adapters with Set Screw**

Available in the following sizes:		
Grub Screw	External Thread	Order Number
M4	M6	RD-TA-GS-4-6
M4	M8	RD-TA-GS-4-8
M6	M8	RD-TA-GS-6-8

